

[Product Information]

Ver.1.2

IMX437LQJ

Diagonal 11.0 mm (Type 2 / 3) CMOS solid-state Image Sensor with Square Pixel for Color Cameras

Description

The IMX437LQJ is a diagonal 11.0 mm (Type 2 / 3) CMOS active pixel type solid-state image sensor with a square pixel array and 2.86 M effective pixels. This chip features a global shutter with variable charge-integration time. This chip operates with analog 3.3 V, digital 1.2 V, and interface 1.8 V triple power supply, and has low power consumption. High sensitivity, low dark current and low PLS characteristics are achieved.
(Applications: FA cameras, ITS cameras)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Global shutter function
- ◆ Input frequency
37.125 MHz / 74.25 MHz / 54 MHz
- ◆ Number of recommended recording pixels: 1936 (H) × 1464 (V) approx. 2.83 M pixels
 - Readout mode
 - All-pixel scan mode
 - Vertical / Horizontal 1 / 2 Subsampling mode
 - ROI mode
 - Vertical / Horizontal - Normal / Inverted readout mode
- ◆ Readout rate
 - Maximum frame rate in
 - All-pixel scan mode: 12 bit: 231.2 frame/s
- ◆ 12-bit A/D converter
- ◆ CDS / PGA function
 - 0 dB to 24 dB: Analog Gain (0.1 dB step)
 - 24.1 dB to 48 dB: Analog Gain: 24 dB + Digital Gain: 0.1 dB to 24 dB (0.1 dB step)
- ◆ I/O interface
 - SLVS (4 ch / 8 ch switching) output (594 / 297 Mbps per ch)
 - SLVS - EC (1 Lane / 2 Lane / 4 Lane / 8 Lane switching) output (2.376 / 1.188 Gbps per Lane)
- ◆ Recommended lens F number: 2.8 or more (Close side)
- ◆ Recommended exit pupil distance: -100 mm to $-\infty$

Pregius

* Pregius is a trademark of Sony Corporation. The Pregius is global shutter pixel technology for active pixel-type CMOS image sensors that use Sony's low-noise CCD structure, and realizes high picture quality.

Sony reserves the right to change products and specifications without prior notice.

Sony logo is a registered trademark of Sony Corporation.

Device Structure

◆ CMOS image sensor			
◆ Image size	Diagonal 11.0 mm (Type 2 / 3)	Approx. 2.86 M pixels	All-pixel
◆ Total number of pixels	1944 (H) × 1496 (V)	Approx. 2.90 M pixels	
◆ Number of effective pixels	1944 (H) × 1472 (V)	Approx. 2.86 M pixels	
◆ Number of active pixels	1944 (H) × 1472 (V)	Approx. 2.86 M pixels	
◆ Number of recommended recording pixels	1936 (H) × 1464 (V)	Approx. 2.83 M pixels	All-pixel
◆ Unit cell size	4.5 μm (H) × 4.5 μm (V)		
◆ Optical black	Horizontal (H) direction: Front 0 pixel, rear 0 pixel Vertical (V) direction: Front 24 pixels, rear 0 pixel		
◆ Package	226 pin LGA		

Image Sensor Characteristics

(T_j = 60 °C)

Item		Value	Remarks
Sensitivity (F5.6)	Typ.	2058 mV	1/30 s accumulation
Saturation signal	Min.	1001 mV	

Basic Drive Mode

Drive mode	Recommended number of recording pixels	Maximum frame rate [frame/s]	Output interface	ADC [bit]
All pixel	1936 (H) × 1464 (V) approx. 2.83 M pixels	121.1	SLVS 8 ch	12
		231.2	SLVS – EC 8 Lane	
Vertical / Horizontal 1/2 subsampling	968 (H) × 732 (V) approx. 0.71 M pixels	425.7	SLVS 8 ch	12
		446.2	SLVS – EC 8 Lane	