SMALL, LOW COST, UNCOOLED INGAAS CAMERA



## Bobcat 320 TE0 and WL series

SWIR cooled camera with 320 x 256 resolution



### SMALL, LOW COST, UNCOOLED InGaAs CAMERA

### **KEY FEATURES**

- ◆ Flexible and easy-to-use
- ♦ Low cost
- ♦ High speed 400 Hz
- ◆ Windowless version optional (WL)

The Bobcat 320 TE0 and WL series are based on an in-house developed, uncooled InGaAs detector with a 320 x 256 pixel resolution. The Bobcat 320 TE0 and WL cameras are offered with GigE Vision interface, 400 Hz maximum frame rate and feature low weight and power.

The Bobcat 320 WL comes with a windowless uncooled detector, specifically targeting laser beam analysis and laser wavefront sensing applications. The cameras have standard on-board image correction featuring non-uniformity correction (NUC), bad pixel replacement (BPR) and automatic gain control (AGC).



# Bobcat 320 TEO and WL series





### **KEY PERFORMANCES**

Image format/Pixel pitch	320 x 256 pixels/20 μm
Detector type	InGaAs photodiode array with CTIA ROIC
Integration type	Snapshot - global shutter
Spectral range	900 - 1700 nm
Max frame rate (full frame)	400 Hz
Power consumption	4 W
Power supply voltage	DC 12 V

### **FUNCTIONS & INTERFACES**

Command and control	GigE Vision
Connector trigger	SMA
Camera dimensions (width x height x length)	55 mm x 55 mm x 74 mm
Optical interface	C-mount or M42
Camera weight	280 gr

### **PRODUCT SELECTOR GUIDE**

XEN-000730 (Bobcat 320 TE0 GigE 400) XEN-000731 (Bobcat 320 WL GigE 400)





in **y** f **b** 

xenics.com

