

**WORLD'S FASTEST InGaAs  
AREA-SCAN CAMERA**



# Cheetah Series

SWIR cooled camera with 640 x 512 resolution



*WORLD'S FASTEST InGaAs  
AREA-SCAN CAMERA WITH  
HIGH IMAGE RESOLUTION*

## **KEY FEATURES**

- ◆ World's fastest SWIR area-scan imaging up to 1700 Hz
- ◆ vSWIR optional
- ◆ Low dark current
- ◆ Reliable data transfer via CameraLink

The Cheetah series is based on an in-house developed, temperature stabilized InGaAs detector with a 640 x 512 pixel resolution. The Cheetah 640 camera with single-stage TE-cooled detector offers high frame rates of either 400 Hz, 800 Hz or 1700 Hz while the version with three-stage TE-cooled detector offers a frame rate of up to 110 Hz.

A visible short-wave infrared (vSWIR) option is available for extension into the visible wavelength band.

# Cheetah Series

EU based supplier



## KEY PERFORMANCES

Image format/Pixel pitch	640 x 512 pixels/ 20 $\mu$ m
Detector type	InGaAs photodiode array with CTIA ROIC
Sensor cooling	TE-cooled
Integration type	Snapshot - global shutter
Spectral range	900 - 1700 nm (SWIR); 500 - 1700 nm (vSWIR)
Max frame rate (full frame)	111 Hz / 444 Hz / 865 Hz / 1730 Hz
Power consumption	Up to 25 W or 60 W
Power supply voltage	DC 12 V

## FUNCTIONS & INTERFACES

Command and control	CameraLink
Connector trigger	SMA
Camera dimensions (width x height x length)	143 mm x 137 mm x 95 mm
Optical interface	C-mount
Camera weight	2000 gr

## PRODUCT SELECTOR GUIDE

XEN-000175 (Cheetah 640 TE1 400)	XEN-000045 (Cheetah 640 TE1 400 vSWIR)
XEN-000577 (Cheetah 640 TE1 800)	XEN-000578 (Cheetah 640 TE1 800 vSWIR)
XEN-000176 (Cheetah 640 TE1 1700)	XEN-000046 (Cheetah 640 TE1 1700 vSWIR)
XEN-000271 (Cheetah 640 TE3)	

[sales@xenics.com](mailto:sales@xenics.com)



[xenics.com](http://xenics.com)

**Xenics**  
Photonis Group

© Xenics. XDS009. The information furnished is believed to be accurate and reliable, but is not guaranteed and is subject to change without notice. No liability is assumed by Xenics for its use. Performance data represents typical characteristics as individual product performance may vary. Customers should verify that they have the most current Xenics product information before placing orders. No claims or warranties are made as to the application of Xenics products. Texts and pictures may no be considered as contractually binding. This document may not be reproduced, in whole or in part, without the prior written consent of Xenics.